


12"x24" Rectified Field Tile



Bianca
100004614 - Honed
100004622 - Polished



White Onyx
100004617 - Honed
100004625 - Polished



Beige Onyx
100004613 - Honed
100004621 - Polished



Grey Onyx
100004615 - Honed
100004623 - Polished



Notte
100004616 - Honed
100004624 - Polished

24"x48" Rectified Field Tile



Bianca
100004627 - Honed
100004632 - Polished




White Onyx
100004630 - Honed
100004635 - Polished



Beige Onyx
100004626 - Honed
100004631 - Polished




Grey Onyx
100004628 - Honed
100004633 - Polished



Notte
100004629 - Honed
100004634 - Polished

2"x2" Mosaic (12"x12" Sheet)



Bianca
100004637 - Honed
100004642 - Polished




White Onyx
100004640 - Honed
100004645 - Polished



Beige Onyx
100004636 - Honed
100004641 - Polished



Grey Onyx
100004638 - Honed
100004643 - Polished



Notte
100004639 - Honed
100004644 - Polished



Gemma

Glazed Porcelain

Photo Features Gemma 12"x24" Rectified Field Tile - Honed in Bianca.


SIZING & PACKAGING

Type	Bianca Item Code	White Onyx Item Code	Beige Onyx Item Code	Grey Onyx Item Code	Notte Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field	100004614	100004617	100004613	100004615	100004616	12"x24"	Rectified Field Tile - Honed	8	15.50
	∅ 100004622	100004625	100004621	100004623	100004624	12"x24"	Rectified Field Tile - Polished	8	15.50
	100004627	100004630	100004626	100004628	100004629	24"x48"	Rectified Field Tile - Honed	2	31.00
	∅ 100004632	100004635	100004631	100004633	100004634	24"x48"	Rectified Field Tile - Polished	2	31.00
Trim	100004658	100004661	100004657	100004659	100004660	3"x24"	Bullnose - Honed	10	-
	∅ 100004663	100004666	100004662	100004664	100004665	3"x24"	Bullnose - Polished	10	-
Mosaic	100004637	100004640	100004636	100004638	100004639	12"x12" Sheet	2"x2" Mosaic - Honed	5	-
	∅ 100004642	100004645	100004641	100004643	100004644	12"x12" Sheet	2"x2" Mosaic - Polished	5	-

ANSI TECHNICAL SPECIFICATIONS


	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥0.42	3	Unaffected	7	≥350 lbf	≤ 0.5%	Unaffected

Shade Variation



APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻	●	◻	◻
Commercial	●	◻	◻	●	◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



This product is artisanal and may possess inherent size and color variation.

For installation of all polished, polished glazed, lappato, and honed porcelain/ceramic tiles, use a grout release prior to grouting to prevent absorption of the grout into the tile's micropores. Use a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the polished or honed tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet or exterior floor applications. Do not use acidic cleaners.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit bedrosians.com for current product information.

