

MSI

Making Dream Surfaces Attainable



Eden
Porcelain Collection
www.msisurfaces.com

| Size | Thickness | EDEN BARDIGLIO |
|----------------|-----------|----------------|
| 12x24 Polished | 3/8" | NEDEBAR1224P |
| 12x24 Matte | 3/8" | NEDEBAR1224 |
| 32x32 Polished | 3/8" | NEDEBAR3232P |
| 32x32 Matte | 3/8" | NEDEBAR3232 |
| 24x48 Polished | 3/8" | NEDEBAR2448P |
| 24x48 Matte | 3/8" | NEDEBAR2448 |
| 4x24 Polished | 3/8" | NEDEBAR4X24BNP |
| 4x24 Matte | 3/8" | NEDEBAR4X24BN |
| 3x3 Matte | 3/8" | NEDEBAR3X3HEX |
| 2x2 Matte | 3/8" | NEDEBAR2X2HEX |

Colors



Edén Bardiglio 12"x24"



Edén Bardiglio 24"x24"

| APPLICATIONS | Flooring | Counters | Wall | PEI Rating | Variation | COF | Breaking Strength | Water Absorption | Hardness |
|------------------|----------|----------|------|------------|-----------|---|-------------------|------------------|----------|
| RESIDENTIAL | ● | ● | ● | III | V3 | DCOF < 0.42 Polished DCOF > 0.42 Matte | > 275 lbf | < 0.5% | 7 |
| LIGHT COMMERCIAL | ● | ● | ● | | | | | | |
| HEAVY COMMERCIAL | | ● | ● | | | | | | |

| Freeze / Thaw | Abrasion Resistance | Chemical Resistance | Rectified/ Non-Rectified | Glazed / Non Glazed |
|---------------|---------------------|---------------------|--------------------------|---------------------|
| Resistant | III | Resistant | Rectified | Glazed |

Acquire the jaw-dropping beauty of natural Edén at a more palatable price point with the porcelain Edén Bardiglio. The rectified ink jet tile is an elegant interpretation of the natural stone that requires virtually no maintenance. The series is available in an impressive array of sizes: 12"x24", 24"x48", 32"x32" and 4"x24" bullnose.

Technical Information

Primary Colors: Grey
 Material Type: Porcelain
 Finish: Polished & Matte
 Polished: Hardness / Mohs 5
 Matte: Hardness / Mohs 7

Features At A Glance

- Luxurious porcelain (Matte and Polished) tiles with authentic marble looks and colorations
- High quality Ink Jet technology

Trim



4" x 24" Bullnose

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.

