

Model: ONA BLANCO MATE 13"X39" approx.

Codes: 100295711

Water absorption: BIII - Revestimiento (10%≤E≤20%)

Finish: Glazed / Standard

Tone variations: V1


Rectified: Yes




DIMENSIONAL FEATURES

| | | |
|-----------------------------|----------------|----------|
| Thickness | 7/16" approx | +/-5%* |
| Width | 13 1/8" approx | |
| Length | 39 3/8" approx | |
| Length and width deviation | Below 0.15% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation | Below 0.15% | +/-0.3%* |
| Surface flatness deviation | Below 0.15% | +/-0.4%* |

FEATURES

 Natural-looking, non-glossy surface finish.

 Name given to the finish of those tiles dimensionally improved after the firing process.

 Finish with clearly defined protrusions that give the surface a feeling of volume.

 Wall installation

MECHANICAL FEATURES

| | | |
|-----------------------------|------------------|----------|
| Breaking strength | 364.79 LBF | >125LBF* |
| Modulus of rupture | 7.87 LBF | >=3LBF* |
| Crazing resistance | Resists 3 cycles | |
| Resistance to thermal shock | RESISTE | |

HYGIENIC FEATURES

| | | |
|---------------------|--|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance | Class 5. Easy cleaning with water | 3 Min.* |

ANTI-SLIP VALUE

| | | |
|--|-----------|--|
| Friction (dry) | No Aplica | |
| Friction (wet) | No Aplica | |
| Dynamic coefficient of friction (dcof) | No Aplica | |

PACKING

| | | |
|------------------------|----------------|--|
| Sales units per box | 14.34 SQF/CS | |
| Sales units per pallet | 630.85 SQF/PAL | |
| Sales units per unit | 3.58 SQF/ST | |

System Certification



Do not use cleaning agents containing hydrofluoric acid.
It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.
For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double gluing technique.
Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

SCOPE OF USE

Technical code-1

1 - Use on walls

System Certification



Do not use cleaning agents containing hydrofluoric acid.
It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.
For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.
Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.