

Model: OLD DARK GRAY 13"X39" approx.

Codes: 100295111

Water absorption: BIII - Revestimiento (10%≤E≤20%)

Finish: Glazed / Standard

Tone variations: V2






Rectified: Yes



DIMENSIONAL FEATURES

| | | |
|-----------------------------|----------------|----------|
| Thickness | 7/16" approx | +/-5%* |
| Width | 13 1/8" approx | |
| Length | 39 3/8" approx | |
| Length and width deviation | Below 0.15% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation | Below 0.15% | +/-0.3%* |
| Surface flatness deviation | Below 0.15% | +/-0.4%* |

FEATURES

-  Natural-looking, non-glossy surface finish.
-  General deshaded design with a degree of color and appearance variation.
-  Name given to the finish of those tiles dimensionally improved after the firing process.
-  Finish with clearly defined protrusions that give the surface a feeling of volume.
-  Wall installation

MECHANICAL FEATURES

| | | |
|-----------------------------|------------------|----------|
| Breaking strength | >1100 | >125LBF* |
| Modulus of rupture | >5.17 LBF | >=3LBF* |
| Crazing resistance | Resists 3 cycles | |
| Resistance to thermal shock | RESISTE | |

HYGIENIC FEATURES

| | | |
|---------------------|--|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance | Class 5. Easy cleaning with water | 3 Min.* |

ANTI-SLIP VALUE

| | | |
|--|-----------|--|
| Friction (dry) | No Aplica | |
| Friction (wet) | No Aplica | |
| Dynamic coefficient of friction (dcof) | No Aplica | |

PACKING

| | | |
|------------------------|----------------|--|
| Sales units per box | 14.34 SQF/CS | |
| Sales units per pallet | 630.85 SQF/PAL | |
| Sales units per unit | 3.58 SQF/ST | |

System Certification



SCOPE OF USE

Technical code-1

1 - Use on walls

System Certification

