


ONDA



Tamaño / Size:	15 x 40 cm / 6" x 16"
Esesor / Thickness:	10 mm
Acabado / Finish:	Brillo / Gloss
Material / Body Type:	Ceramic Tile - group BIII





ABSORCIÓN AGUA / WATER ABSORTION

	Absorción de Agua / Water Absorption	ISO 10545-3 ASTM C373	E > 10%
---	--------------------------------------	--------------------------	---------



CARACTERÍSTICAS DIMENSIONALES / BODY TECHNICAL SPECIFICATIONS

	Longitud y Anchura / Length and Width	ISO 10545-2 ASTM C499	± 0,6% / ± 2,0mm
	Esesor / Thickness	ISO 10545-2 ASTM C499	± 5% / ± 0,5mm
	Rectitud de los lados / Straightness of sides	ISO 10545-2 ASTM C485	± 0,5% / ± 1,5mm
	Planitud de la superficie / Surfaces Planarity	ISO 10545-2 ASTM C485	± 0,5% / ± 2,0mm
	Ortogonalidad / Squareness - Rectangularity	ISO 10545-2 ASTM C502	± 0,5% / ± 1,5mm
	Apecto superficial / Surface Quality	ISO 10545-2	>95%

CARACTERÍSTICAS MECÁNICAS / MECHANICAL TECHNICAL SPECIFICATIONS

	Dilatación térmica lineal / Lineal Thermal Expansion	ISO 10545-8 ASTM C372	Pass
	Choque térmico / Thermal shock	ISO 10454-9	Pass

CARACTERÍSTICAS QUÍMICAS / CHEMICAL CHARACTERISTICS

	Resistencia química de alta concentración / High Concentration Chemical Resistance	ISO 10545-13 ASTM C650	GHA
	Resistencia química de baja concentración / Low Concentration Chemical Resistance	ISO 10545-13 ASTM C650	GLA
	Productos de limpieza domésticos / Domestic cleaning products and swimming pool salts	ISO 10545-13 ASTM C650	GA
	Resistencia a las Manchas / Stain Resistance	ISO 10545-14 ASTM CTI 81-7	5