

Series **Slant**



Slant Sand Mate 40x120 Rc

40x120 RC



Technical Data



Series: SLANT

Paste Type: Pasta Blanca

Product: Slant Sand Mate 40x120 Rc

Slip Resistance R:

Format: 40x120 RC

Class: Clase 1

Sales Group: G.181

UPEC:

Type: WALL TILE

Finish: MATE

Format	Product Type	Pcs/box	m ² /box	Kg/box	Boxes/pallet	m ² /pallet	Kg/pallet
40x120 RC	Base	3	1,440	26,650	20,000	28,800	533,000

SLANT

Notice: the contents of this packaging list are indicative; actual packaging contents may vary. Please consult our sales representatives for the exact details.

Technical Data Sheet

Slant Sand Mate 40x120 Rc



Family:	MATTE WALL TILE
Absorption Group:	BIII
Format:	40x120 RC
Manufacturing Dimensions (mm):	1200 x 400 x 10,8

PHYSICAL CHARACTERISTICS

CHARACTERISTIC	STANDARD	VALUE
Dimensional tolerances and surface appearance	UNE-EN-ISO 10545-2	COMPLIES WITH STANDARD
Water absorption	UNE-EN-ISO 10545-3	E>10%
Breaking strength (N)	UNE-EN-ISO 10545-4	>600
Flexural strength (N/mm ²)	UNE-EN-ISO 10545-4	>=12
Thermal shock resistance	UNE-EN-ISO 10545-9	COMPLIES WITH STANDARD
Crazing resistance	UNE-EN-ISO 10545-11	COMPLIES WITH STANDARD
Frost resistance	UNE-EN-ISO 10545-12	INTERIOR USE ONLY
Moisture expansion (mm/m)	UNE-EN-ISO 10545-10	0,2
Linear thermal expansion from 200°C to 1000°C	UNE-EN-ISO 10545-8	5,2x10 ⁻⁶ °C ⁻¹
Reaction to fire	UNE-EN-ISO 13501-1	A1
DCOF	DCOF	

CHEMICAL CHARACTERISTICS

CHARACTERISTIC	STANDARD	VALUE
Stain resistance	UNE-EN-ISO 10545-14	COMPLIES
Resistance to chemical products and pool salts	UNE-EN-ISO 10545-13	COMPLIES
Resistance to high-concentration acids and alkalis	UNE-EN-ISO 10545-13	MIN HB
Resistance to low-concentration acids and alkalis	UNE-EN-ISO 10545-13	MIN LB